

SECTION

22.0.0 Masonry Construction

22.1.0 Minimum Requirements

The minimum requirements for all masonry construction shall comply with "Recommended Building Code Requirements for Engineered Brick Masonry" Structural Clay Products Institute, 1520 - 18th St., N.W. Washington, D.C.

22.2.0 Prior Approval - Used Brick or Masonry Units

Any previously used brick or masonry units, of whatever type, shall first be accepted by the Building Commissioner. Samples of used brick or masonry to be used shall be submitted with the building permit application.

22.3.0 Exterior Brick

Only brick (solid masonry units, made from clay or shale) complying with ASTM C-216 grades shall be used for exterior brick work.

22.4.0 Firebrick

Firebrick shall comply with ASTM C-106 or F.S. HH-R-191.

22.5.0 Miscellaneous Masonry Materials Compliance:

22.5.1 Ceramic Glazing Tile or Facing Brick: ASTM C-126.

22.5.2 Structural Clay Floor Tile: ASTM C-57 or F.S. SS-T-321.

22.5.3 Ceramic Tile: F.S. SS-T-308.

22.5.4 Concrete Masonry Units - Catch Basins and Manholes: ASTM C-139.

22.5.5 Precast Reinforced Concrete Culvert, Storm Drain and Sewer Pipe: ASTM C-76

22.5.6 Drain Tile: ASTM C-4 or ASTM C-412.